

Flaggstång

	6,6 m	8 m	9 m	10 m	12 m	14 m	16 m
Vikt, flaggstång (kg)	23	26	28	35	40	65	75
Topp diameter (mm)	75	65	65	65	65	65	65
Botten diameter (mm)	120	120	128	135	148	163	177
Godstjocklek, flaggstång (mm)	Ca 3,0	Ca 3,0	Ca 3,0	Ca 3,5	Ca 3,5	Ca 4,5	Ca 4,5

Tillbehör

	Toppkula, plexiglas & plast (mm)	135	135	135	135	135	135	135
	Toppkula, metall guld/silver (mm)	120	120	120	150	150	180	180
(A)	Höjd till knap & läsbar lucka (mm)	1400	1400	1400	1400	1400	1400	1400
(B)	Avstånd till vev, alt 1 (mm)	900	900	900	900	900	900	900
(C)	Avstånd till vev, alt 2 (mm)	550	550	550	550	550	550	550
(D)	Armerad utvändig flagglina (ø mm)	5,0	5,0	5,0	5,0	5,0	5,0	5,0
(D)	Draghållfasthet, flagglina 5 mm (kg)	600	600	600	600	600	600	600
(D)	Längd på flagglina 5 mm (m)	16	16	16	23	23	35	35
(E)	Knap längd (mm)	165	165	165	165	165	165	165
(E)	Fästhål Knap, CC mått (mm)	33,5	33,5	33,5	33,5	33,5	33,5	33,5

Teknisk info

()	Stålrörets längd (mm)	1600	1600	1600	2000	2000	2000	2000
()	Stålrörets godstjocklek (mm)	3,0	3,0	3,0	4,0	4,0	5,0	5,0
()	Ytterdiameter, Stålrör (mm)	102	102	102	121	121	145	154

